

AmberLink™

Professional Personal Emergency Response and Safety Monitoring System



Visonic's AmberLink comprehensively answers central monitoring stations' needs for a wireless, reliable and cost-effective emergency and safety response system. With a clear audio communication channel and varied safety detectors, AmberLink enables central monitoring stations to receive emergency calls and to accurately assess the customer's situation from remote.

Designed for people with special needs, AmberLink is easy to use and supported by a wide variety of emergency and safety devices. Emergency calls to the central monitoring station or a private phone can

be initiated by pressing the large emergency button on the console or by pressing one of the portable or wearable buttons from anywhere in the premise. Additionally, emergency calls can be automatically activated upon detection of a safety threat. Support for both PSTN and optional GSM communication interfaces maximizes reliability.

With up to 28 different wireless inputs, AmberLink can comprehensively monitor for safety threats, including smoke, flood and carbon monoxide (CO). PIR detector support enables programmable inactivity monitoring.



Visonic®

For a secure way of life

Personal safety and lifestyle support

- Emergency call initiation options:
 - Large HELP button on the console
 - Portable and wearable remote pendant which can be activated from anywhere in the premises
 - Automatic initiation by the central station - upon inactivity detection
- Optional internal GSM communication module
- Built-in, two-way, high-volume speakerphone
 - High-volume setting
 - High-sensitivity microphone - enables a frail voice to be heard, even from afar

Home safety and security monitoring

- Supports up to 28 wireless transmitters
- Comprehensive environmental safety detection, including smoke, flood and carbon monoxide (CO)

Flexible, user-friendly system

- Intuitive HHPC utility enables system programming on-site* and easy remote programming
- USB interface for local programming
- Management via telephone line or over cellular network

Highly reliable

- Power failure and low/missing battery alerts
- 34-hour backup battery
- Programmable periodic test
- Low-battery indicator on emergency transmitters

Sleek design for modern lifestyles

- Ultra-modern, streamlined design fits any décor
- Large buttons ensure easy, confident use

*Requires PC/laptop running Windows 2000 or later

Wide range of safety, security and home protection accessories:**



Emergency Button



Wristband Transmitter



Magnetic Contact



Motion Detector



Range Extender



CO Detector



Curtain Detector



Flood Detector



Temperature Detector



Smoke Detector

Specifications

Weight:	1.35kg (3lb)
Dimensions:	248 x 185 x 55mm (9-13/16 x 7-1/4 x 2-5/16in)
Main Power:	120 VAC, 60 Hz / 9VAC, 700mA (USA) 230 VAC, 50 Hz / 9VAC, 700mA (Europe)
Reporting modes:	Contact ID, SIA, PULSE
Color:	Off-white
Back-up battery:	34 hours back-up
Battery type:	Ni-MH, 7.2V, 1.3Ah
Transmitters:	up to 28 can be assigned
Operating temperatures:	0°C to 49°C (32°F to 120°F)

**Partial list; actual design may be different from the design in the images.

• Visonic and Amber are registered trademarks of Visonic Ltd. Other names are the property of their owners. Visonic reserves the right to change information or specifications without notice.

VISONIC LTD. AMBER LINK DATA SHEET ENG C-800767 (Rev.02)



Visonic®
For a secure way of life

•Head Office Israel Tel (+972) 3 645 6789 •Spain Tel (+34) 91 659 3120 •U.S.A Tel +1 (860) 243 0833
•U.K. Tel +44 (0) 845 0755 800 •Germany Tel (+49) 211 600 6960 •Nordic Tel (+47) 6758 0843
•Poland Tel (+48) 22 639 3436

For more information, visit us at: www.visonic.com or info@visonic.com