

Emergency Response and Personal Safety Monitoring System



AVAILABLE!

869 MHz European
Social Alarm
Frequency



AmberClassic

Maintaining the ability to live an independent lifestyle, in one's own home or in an independent-style protected living arrangement, is a central element in today's attitudes to aging. People are living longer, often needing to cope without family to help in their daily lives. As their health declines over time, home-based safety and health monitoring technologies can make all the difference - enabling seniors to live safely and comfortably at home and relieving their adult children of worry.

Amber®Classic, from Visonic, provides a complete, highly flexible solution for enhancing the safety and comfort of aging seniors as well as other people needing reassurance. It includes a full array of home and personal safety alarms that detect dangers such as carbon monoxide (CO), smoke, floods and intrusions, as well as falls and unusual inactivity that may indicate a problem. Alerts and a large emergency button provide immediate connection to an emergency response service or designated personal contact.



Visonic®

For a secure way of life

AmberClassic

Personal safety

- One-button emergency dialing to a medical center or private number
- Fall monitoring via wearable detector
- Customizable inactivity monitoring, enabling notification of deviations from normal daily activities
- Remote emergency button activation
- Emergency call initiation and pick-up of incoming calls using wearable remote transmitters
- Built-in, two-way, high-volume speakerphone
- High volume setting - ideal for hard-of-hearing
- High-sensitivity microphone - enables a frail voice to be heard even from afar
- Up to 16 customizable voice and display reminders - for medicines, food, appointments, etc.

Home safety and security monitoring

- Comprehensive environmental safety detection, including smoke, flood and carbon monoxide (CO)
- Intrusion monitoring option

Flexible, user-friendly system

- Intuitive HHPC utility enables system programming on-site* and easy remote programming and management via telephone line
- Large LCD screen with unlimited language options
- Console can be configured to support up to either 29 or 255 wireless transmitters (for private homes or group living facilities respectively)
- Fully upgradeable software - supports additional languages, capabilities
- Optional: AmberClassic-x model without LCD screen

Highly reliable

- Power failure and low/missing battery alerts
- 24-hour backup battery
- Programmable periodic test
- Low-battery indication for pendants

*Requires PC/laptop running Windows 2000 or later

Specifications:

Weight:	1.35kg (3lb)
Dimensions:	248 X 185 X 55mm (9-13/16 X 7-1/4 X 2-5/16in)
Main Power:	120VAC, 60Hz / 9VAC, 700mA (USA) 230VAC, 50Hz / 9VAC, 700mA (Europe)
Reporting modes:	Contact ID
Color:	Off-white
Back-up battery:	24 hours back-up
Battery type:	Ni-MH, 9.6V, 1.8Ah
Transmitters:	up to 29 can be assigned
Operating temperatures:	0° to 49°C (32° to 120°F)
Standards:	UL compliant, EN 50134-3 Social Alarm, EN 300220 Class1

Wide range of personal safety and security accessories*:



Necklace Transmitter



Wristband Transmitter



Emergency Button



Fall Detector




Flood Detector



Smoke Detector



CO Detector



Motion Detector



Magnetic Contact



*The actual design may be different to the design in the images.

Visonic and Amber are registered trademarks of Visonic Ltd. Other names are the property of their owners. Visonic reserves the right to change information or specifications without notice.

VISONIC LTD. AMBER CLASSIC 869 MHz 2008 DATA SHEET ENG C-800560 (Rev.00)

Designed by: Linor Ankri



Visonic[®]
For a secure way of life

•Head Office Israel Tel (+972-3) 645 6789 •Spain Tel (+34-91) 659 3120 •U.S.A Tel (+860) 243 0833
•Hong Kong Tel (+852) 2157 7147 •U.K. Tel (+44-870) 730 0800 •Germany Tel (+49) 211 600 6960
•Nordic Tel (+47) 6758 0843 •Poland Tel (+48-22) 639 3436 •South Africa Tel (+27) 84 577 8668
For more information, visit us at: www.visonic.com or info@visonic.com