



WIRELESS

MCM-140

Universal Wireless Remote Commander for PowerMax™

The MCM-140 enhances the ease of use and the control of all functions of the wireless PowerCode™, PowerMax™, home automation and security system.

In-house wireless remote control of PowerCode™ and PowerMax™ systems

Easy programming and user-friendly control

Visual indications with three color-coded LEDs

Audible signals given in response to specific actions

Back light illumination

Modern, ergonomic design for hand held use or wall mounting, anywhere in the home or office

 **Visonic**®
For a smart and secure lifestyle



MCM-140 PowerMax™ Wireless Remote Commander

- Choice of operating frequencies to comply with international demand
- Different channel for each command
- Fully supervised
- Long-life 3 V standard lithium battery
- Automatic reporting of low battery condition
- Wall-mounting bracket included
- Compliance with the latest European standards

WIRELESS

Visonic's MCM-140 is the universal wireless remote control unit for the PowerMax™ home automation and security control system. It enables easy programming and control of the many PowerMax™ functions from anywhere in the home or office.

MCM-140 functions and commands are activated in the same manner as on the PowerMax™ keypad for controlling events or X-10 devices from any room or throughout the facility. Employing Visonic's PowerCode™ and Code Secure™ technologies, the MCM-140 sends different coded signal (channel) for each function or command. The MCM-140 can also be used with other Visonic PowerCode™ wireless systems.

The keypad's backlit illumination enables operation even in the dark. Color-coded LEDs and audible sounds confirm the user's command. Automatic supervision messages are sent periodically to confirm connectivity.

This compact, ergonomically designed controller operates at several optional frequencies in compliance with European and U.S. standards. It has a 3V long life standard lithium battery with automatic reporting when the battery needs to be replaced. The wall-mounted bracket assures that the remote control unit is conveniently located where you most often need it.

SPECIFICATIONS

- Transmitted ID Type:** PowerCode™ and CodeSecure™
PowerCode™ - Used for Lights 1-7, Light 8 (PGM controlled), Fire and Emergency functions
CodeSecure™ - Used for Home arming, Away arming, Disarming, Aux and Panic functions
Operating Frequency (MHz): 315, 433.9, 868.95 and 869.2625
Battery: 3 V standard Lithium battery, CR123A
Back light illumination: Selectable on/off
Dimensions (HxWxD): 127 x 70 x 24 mm (5 x 2-3/4 x 31/32 in.)
Operating Temperatures: 0° -49°C (32° -120°F)
Compliance with Standards: FCC part 15, Industry Canada, EN 50130-4, 300220-3

Visonic Ltd reserves the right to change specifications without prior notice.
Full warranty statement available upon request.

Head Office (Israel)
Visonic Inc. (U.S.A.)
Visonic Ltd (U.K.)
Visonic Iberica (Spain)
Visonic GmbH (Germany)
Visonic SARL (France)
Visonic Deson (East Asia)
Visonic Rep. (Nordic Countries)
Visonic Rep. (Latin America)

Tel (972-3) 645 6789
 Tel (800) 223 0020
 Tel (44-870) 730 0800
 Tel (34-91) 659 3120
 Tel (49-2202) 104 930
 Tel (33-1) 5334 3223
 Tel (852) 2157 7142
 Tel (47) 6758 0843
 Tel (972-3) 645 6721

Fax (972-3) 645 6788
 Fax (860) 242 8094
 Fax (44-870) 730 0801
 Fax (34-91) 663 8468
 Fax (49-2202) 104 959
 Fax (33-1) 4655 6136
 Fax (852) 2512 9071
 Fax (47) 6758 0814
 Fax (972-3) 645 6788

W e b s i t e : <http://www.visonic.com>



Visonic®

For a smart and secure lifestyle