



General Advisory

PowerManage v. 4.6



Date: Tuesday, June 2, 2020

Region: EMEA, APAC

Product: PowerManage

Brand: Tyco | Visonic

All-in-one receiver, technical management center, and interactive service platform.

Overview

We are pleased to announce the release of version 4.6 of the PowerManage Platform. In addition to many system improvements this version of PowerManage adds in support of the latest version of the PowerSeries Neo and PowerSeries Pro.

Features, Benefits & Value

Feature	Benefit	Value
Panel support	Supports the latest version of the PowerSeries Pro. (v. 1.2)	In addition to many other system improvements The PowerSeries Pro v. 1.2 now supports up to 32 partitions and 32 keypads. (See PowerSeries Pro release notes for a complete description)
Visual Verification images on demand (PowerSeries Pro & Neo)	Receives additional images from PIR Cams on demand.	After an alarm has been received at the central monitoring station that includes visual verification, additional images can be requested to obtain more site information.
Panel support	Supports the latest version of the PowerSeries Neo. (v. 1.35)	The latest version PowerSeries Neo supports native support of all newer PowerG sensors and improved user experience with fire zones types. (see PowerSeries Neo release notes for a complete description)

Universal Communicator support	Supports the upcoming DSC TL405LT & Bentel BLE320 communicators.	By being able to control outputs on the Universal Communicator the end user can now arm/disarm their existing Intrusion panel along with receive notifications using inputs from the communicator.
Encryption reset for DSC PowerSeries Neo and Pro.	Allows the encryption key to be reset in the event of a break in communication between the panel and the PowerManage server.	Ensures protection for all IP communications.
60 minute timeout for receiving visual verification images	Increases the time PowerManage waits to receive all images from a location.	Increases the ability to receive all images when slow network connectivity occurs.
Dark Mode support	Full support of Dark Mode while using PowerManage web interface.	Dark Mode reduces the amount of blue light end-users are exposed to.
Improved discovery progress bar	More intuitive display showing progress.	Easier for user to identify status of discovering panel.
Additional system settings	Several system settings moved to web interface.	Easier for user to manage their server.
Hebrew language support	Additional language support.	Can now be used by all Hebrew speakers.

Compatibility

PowerMaster 10/30/33: v.16, v.17, v.18.x, v.19.2, v.19.3, v.19.4, v.20.2

PowerMaster 360/360R: v.19.3, v.19.4, v.20.2

PowerLink: x.x.42, x.x.46, x.x.58, x.x.72, x.x.89, 7.x.92.4, 7.x.92.6, x.x.93.22, x.x.94.14

PowerSeries Neo: 1.11, 1.14, 1.2, 1.31, 1.33, 1.35

PowerSeries Neo communicator: 4.11, 5.01, 5.02, 5.03, 5.11, 5.21, 5.3, 5.41

PowerSeries Pro: 1.02.01.001, 1.11.01.002, 1.20.xx.xxx

Availability

Please contact your local sales rep for more information.

Contact Information	
Order Entry	Contact your local sales rep. or email markvisonic@tycosp.com
Sales	Contact your local sales rep. or email markvisonic@tycosp.com
Technical Support	EMEA - Local: +31 475 352 722 EMEA - Toll Free: 800-22558926 APAC - Local Direct Dial Numbers: India: +91-80-4199-0994 China: +86-21-6163-8644 Australia: +61-28-317-1322 Oceania and New Zealand: +64-9942-4004 Local Toll Free Numbers: Australia: 1-800-580-946 China: 400-6711-528 or email: intrusion-support@jci.com
Product Manager	Neil Evans Neil.evans@jci.com



Johnson Controls

5757 N. Green Bay Avenue | P.O. Box 591 Milwaukee, WI 53201 | 441-524-1200